

**Currency :**

**Discount :**

**No. QTY. PACKING ITEM CODE PRODUCT DESCRIPTION Unit Price Avail.**

■ **System: UNDEFINED CATALOGUE [\*]**

Particulars :  
Serial No :

■ **Subsystem: UNDEFINED GROUP [\*]**

1.	6. PC		11/7 Oil Seal		
2.	6. PC		11/8 Oil Level Gauge		

■ **System: DIESEL GENERATOR ENGINE DAIHATSU 6DK-20 (PC/PU) [6DK-20]**

Particulars : 4-cycle, FW cooled diesel engine "6DK-20", 740 kW (1,007 PS) ? 900 min<sup>-1</sup>, FO consumption: 197 g/kW/h (145 g/PS/h) + 5 % (at 100 % load, Hu = 42.7 MJ/kg) (with NOx emission control),  
\* Turbocharger with cleaning device of blower and turbine side "RH-163 (TUS)"  
\* Air cooler "DH48HZ"  
\* LO pump (14.8 m3/h) and LO cooler (12 m2)  
\* Diesel oil feed pump (0.48 m3/h)  
\* Cooling fresh water pump for jacket water (36 m3/h)  
\* Governor "RHD6-MC (BOSCH)" Hydraulic type  
Maker : DAIHATSU / Serial No : [DK620Z1535] [DK620Z1536] [DK620Z1537]

■ **Subsystem: GOVERNOR DRIVING DEVICE RHD 6 (900rpm) [3-25.1]**

3.	3. PC	Z560209031ZZ	O-RING		
----	-------	--------------	--------	--	--

■ **Subsystem: GOVERNOR LINK (RHD 6) [3-28.1]**

4.	3. PC	E204650380	NUT, CONNECTION ROD		
5.	3. PC	E204650410	SPHERICAL PLAIN BEARING		

Form Contains 33 Items

Produced on: 09/01/2018

Currency :

Discount :

No.	QTY.	PACKING	ITEM CODE	PRODUCT DESCRIPTION	Unit Price	Avail.
-----	------	---------	-----------	---------------------	------------	--------

■ **System: DIESEL GENERATOR ENGINE DAIHATSU 6DK-20 (PC/PU) [6DK-20]**

Particulars : 4-cycle, FW cooled diesel engine "6DK-20", 740 kW (1,007 PS) ? 900 min<sup>-1</sup>, FO consumption: 197 g/kW/h (145 g/PS/h) + 5 % (at 100 % load, Hu = 42.7 MJ/kg) (with NOx emission control),  
 \* Turbocharger with cleaning device of blower and turbine side "RH-163 (TUS)"  
 \* Air cooler "DH48HZ"  
 \* LO pump (14.8 m3/h) and LO cooler (12 m2)  
 \* Diesel oil feed pump (0.48 m3/h)  
 \* Cooling fresh water pump for jacket water (36 m3/h)  
 \* Governor "RHD6-MC (BOSCH)" Hydraulic type  
 Maker : DAIHATSU / Serial No : [DK620Z1535] [DK620Z1536] [DK620Z1537]

■ **Subsystem: GOVERNOR LINK (RHD 6) [3-28.1]**

6.	3. PC	E204650450	LINK PIN		
7.	3. PC	E204650460	LINK PIN		
8.	3. PC	E204650580	SPRING		
9.	3. PC	X225110000ZZ	CASTLE NUT		
10.	3. PC	X300010000ZZ	FLAT WASHER		
11.	3. PC	Z300010000ZZ	FLAT WASHER		
12.	3. PC	Z320002030ZZ	SPLIT PIN		

■ **System: GOVERNOR ZEXEL RHD6-MC (PC/PU) [RHD6-MC]**

Particulars : - Governor "RHD6-MC (BOSCH)" Hydraulic type, Control force: 5.9 J {0.6 kgf-m}, Output shaft torque: 9.8 N-m {1.0 kgf-m}, Output shaft operation angle: 35°, Power piston diameter: Small: φ17.7; Large: φ25, Controlled speed range: Standard rating: 600 ~ 2,000 r/min, (Normal: 1,700 - 2,000 r/min), High speed rating: 800 ~ 2,400 r/min, (Normal: 1,900 - 2,400 r/min), Maximum allowable speed 2,500 r/min, Compensator: Needle valve type, Speed droop adjustment range: 0 ~ approx 10% (rated), Direction of rotation: Clockwise & counterclockwise, Hydraulic fluid: SAE20W-40 (Mobiloil), Dry weight (lever type): 5.5 kg, Governor drive power: Max approx 0.2 kW {0.3ps}  
 Maker : ZEXEL / Serial No : [78140618] [78140614] [78240621]

■ **Subsystem: PART LIST RHD-LC type hydraulic governor [PARTS]**

MANUAL 526 E-1, PAGE 161 [ON PDF] OR 25 [ON MANUAL]

13.	1. PC	1	Base		
14.	3. PC	10	O-ring		
15.	6. PC	104	Gasket		
16.	6. PC	112	Gasket		
17.	6. PC	119	O-ring		
18.	6. PC	123	Gasket		
19.	3. PC	13	Sleeve		
20.	6. PC	130	Gasket		
21.	3. PC	131	Regulating valve		
22.	6. PC	18/9	O-ring		
23.	3. PC	2	Needle roller bearing		
24.	3. PC	3	Oil seal		
25.	3. PC	50	Flyweight		
26.	3. PC	51	Washer		
27.	3. PC	52	Thrust needle roller bearing		
28.	3. PC	61	Pin		
29.	3. PC	62	Split pin		
30.	2. PC	7	Gear shaft		
31.	3. PC	89	Roll pin		
32.	3. PC	95	Floating lever		

**Currency :**

**Discount :**

**No. QTY. PACKING ITEM CODE PRODUCT DESCRIPTION Unit Price Avail.**

■ **System: GOVERNOR ZEXEL RHD6-MC (PC/PU) [RHD6-MC]**

Particulars : - Governor "RHD6-MC (BOSCH)" Hydraulic type, Control force: 5.9 J {0.6 kgf-m}, Output shaft torque: 9.8 N-m {1.0 kgf-m}, Output shaft operation angle: 35°, Power piston diameter: Small:  $\phi$ 17.7; Large:  $\phi$ 25, Controlled speed range: Standard rating: 600 ~ 2,000 r/min, (Normal: 1,700 - 2,000 r/min), High speed rating: 800 ~ 2,400 r/min, (Normal: 1,900 - 2,400 r/min), Maximum allowable speed 2,500 r/min, Compensator: Needle valve type, Speed droop adjustment range: 0 ~ approx 10% (rated), Direction of rotation: Clockwise & counterclockwise, Hydraulic fluid: SAE20W-40 (Mobiloil), Dry weight (lever type): 5.5 kg, Governor drive power: Max approx 0.2 kW {0.3ps}  
Maker : ZEXEL / Serial No : [78140618] [78140614] [78240621]

■ **Subsystem: PART LIST RHD-LC type hydraulic governor [PARTS]**

MANUAL 526 E-1, PAGE 161 [ON PDF] OR 25 [ON MANUAL]

33. 3. PC 96 Wire

<hr/>	
<b>TOTAL PRICE</b>	0.00
<b>TOTAL DISCOUNT</b>	0.00
<hr/>	
<b>NET TOTAL</b>	<b>0.00</b>

Form Contains 33 Items